



EFC2200 iSCSI to Fibre Channel Bridge

A high performance, cost effective iSCSI to
Fibre Channel bridge

Product Features:

- 2 x 1Gb Ethernet Ports
- 2 x 4Gb Fibre Channel Ports
- Up to 16,000 Initiators
- Non-Blocking Cache
- Error Recovery Level 2
- iSNS
- Jumbo Packet Support
- Multipath I/O
- GUI Interface

EFC2200 iSCSI to Fibre Channel Bridge

The EFC2200 iSCSI to Fibre Channel Bridge is a high performance protocol bridge for connecting iSCSI based Servers to Fibre Channel enabled peripherals such as Disks, Tape Drives, Tape Libraries and Optical devices

The EFC2200 is housed in an industry standard 1U 19" rack mount enclosure with integral power supplies and cooling. Connectivity to the IP Network is via 2 auto-sensing 1Gb Ethernet ports that can detect the network connection speed, whilst the Fibre Channel Network is connected via 2 4Gb auto-sensing ports.

Managing and installing the EFC2200 could not be easier with its inbuilt intuitive GUI that is easy to use and provides the user with on screen help where necessary.

Key Advantages

Total Flexibility The need to have separate peripherals for both iSCSI and Fibre Channels SANs no longer applies when deploying the EFC2200. With the EFC2200, any Fibre Channel device can be accessed from the iSCSI SAN appearing as though it was part of the iSCSI SAN.

Performance The EFC2200 has many unique features to maximise performance and ensure your data is transferred to the peripheral devices in the shortest possible time. With its load balancing MPIO* enabled Ethernet ports and two 4Gb Fibre Channel ports in combination with its unique non-blocking data cache module the EFC2200 provides industry leading performance.

Recoverability Ensuring that your data reaches its final destination is important these days with tight backup windows. With Error Recovery Level 2 support, the EFC2200 can continue to receive data even if one of the Ethernet connections is disconnected.

Return on Investment Maximising the return on any investment has always been critical. By using the EFC2200 to connect existing Fibre Channel devices to the iSCSI Network not only maximises your investment but also adds a new level of functionality and flexibility.

AVAX INTERNATIONAL

PO Box 542
Hillsburgh, Ontario N0B 1Z0 Canada
Tel: (647) 367-1039 or (877) 401-1892
Fax: (647) 438-2242
www.avax.com



Specifications

Ethernet Ports

| | |
|---------------------|------------------------------|
| Connection | 2 x 1Gbe RJ45 |
| Speed | Auto-sensing 10/100/1000Mb/s |
| Error Recovery | ERLO, ERL1, ERL2 |
| Maximum Packet Size | 16Kb |
| Maximum Initiators | 16,000 |
| Standards | IPv4, iSCSI, iSNS, CHAP, |

Fibre Channel ports

| | |
|--------------------|---|
| Connection | 2x 4Gb SFP NL_port, FL_port, F_port, N-port |
| Speed | Auto-sensing 1/2/4Gb/s |
| Maximum Block Size | 1MB |
| Standards | FC-AL FC-PLDA FC-TAPE FC-PH FC-FLA FCP-SCSI FC-FS |

Indicators

| | |
|-------------------|--|
| Visual Indicators | Power, Network Activity, Link Present, Network Speed, Fibre Channel Activity |
|-------------------|--|

Physical

| | |
|-----------------------------|-----------------------------|
| Enclosure Form Factor | 19 " 1U Rack Mount |
| Dimensions | L 179 mm: W 437mm: H 44 mm |
| Operational Temperature | 0 to 40°C |
| Non-Operational Temperature | -20° to 60°C |
| Power Consumption | 110-230Vac: 25-Watts approx |

Available from: