



www.avax.com



VXA-1 Tape Drive

VXA™ revolutionizes the tape storage industry by using technology similar to that already proven in the networking, Internet and rewriteable CD markets. VXA-1 sets a new standard for data restore and interchange while offering extraordinary tape drive performance.

Discrete Packet Format™ (DPF)

The enabling foundation of VXA technology is its revolutionary Discrete Packet Format. DPF enables data to be written and read in packet form, providing users a data restore capability unprecedented in the storage industry. The packets are uniquely addressed and can be read in any sequence.

Variable Speed Operation™ (VSO)

Conventional streaming drives must operate at a constant speed, and when the flow of data to or from the drive is interrupted, the tape must be stopped and repositioned. This “backhitching” significantly accelerates media and head wear, which in turn adversely impacts data reliability and the life of the drive mechanism. In contrast, the VXA-1 drive adjusts tape motion to match the host transfer rate, eliminating “backhitching.” This capability significantly enhances media and drive reliability while optimizing backup and restore job times.

OverScan Operation™ (OSO)

OverScan Operation is a technique for reading data packets independent of track shape or geometry. By reading packets with multiple scans, VXA virtually guarantees data restore. This also ensures media interchange – data on any VXA tape can be read by any VXA drive.

Please visit www.avax.com to learn more about VXA technology

It's all about restoring your data.™

Re-INVENTING Tape Storage

- 66 GB at 6 MB/sec
- Designed for 100% reliable restore
- Optimal backup and restore job times
- Assured media interchange
- A new standard in data storage value



VXA-1 specifications



PERFORMANCE

CAPACITY	V17 cartridge 66 GB* (33 GB native) V6 cartridge 24 GB* (12 GB native)
SUSTAINED TRANSFER RATE	Host Matching up to 6 MB/sec* (3 MB/sec native)
BURST TRANSFER RATE	Synchronous Burst Rate: 10 MB/sec Asynchronous Burst Rate: 5 MB/sec
DATA COMPRESSION	ALDC Hardware
DATA BUFFER SIZE	4 Mbits
INTERFACE	SCSI-2 single-ended, fast and narrow

RELIABILITY

PACKETIZED DATA	64 bytes of user data plus ECC
ERROR CORRECTION	4-layer Reed Solomon ECC
MTBF	300,000 hours
MTTR	30 minutes
HARD ERROR RATE	< 1 in 1 X 10 ¹⁷ bits
WARRANTY	3 years

ENVIRONMENTAL

OPERATING TEMPERATURE	+5° C to +40° C
NON-OPERATING TEMPERATURE	-40° C to +60° C
RELATIVE HUMIDITY	20% to 80% non-condensing

PHYSICAL

DIMENSIONS (H x W x D)	Internal: 1.63 in. x 5.75 in. x 8.0 in. (41mm x 146mm x 203mm) External: 3.38 in. x 8.93 in. x 11.25 in. (86mm x 227mm x 285mm)
WEIGHT	Internal: 2.2 lbs. (1kg) External: 6.6 lbs. (3kg)
COLOR	White or black

POWER

INTERNAL	Requirement: +5 VDC, +12 VDC Consumption: 8 watts typical
EXTERNAL	Requirement: universal auto-switching, 96 to 240 VAC Consumption: 12 watts typical

VXAtape

CARTRIDGE	V17: 66 GB* (33 GB native), 170m V6: 24 GB* (12 GB native), 62m
MEDIA TYPE	Advanced Metal Evaporated
DURABILITY	20,000 passes
SHELF LIFE	30 years

VXA SUPPORT

VXA-1 products from Ecrux Corporation set a new standard for tape drive value, reliability and data availability. Because we recognize product support as an essential component of customer satisfaction, all VXA-1 products come with exceptional support services, including:

- 3-year warranty
- Free phone support during the warranty period
- Fast, user-friendly website with practical solutions

SOFTWARE COMPATIBILITY

The VXA-1 is compatible with all major backup applications and operating systems. For up-to-date compatibility information, please visit our website at www.vxatape.com.

*Compressed specifications assume a 2:1 compression ratio. Compression, capacity and throughput will be dependent upon the type of data and system configuration. All specifications are subject to change without notice.

© Copyright Ecrux 1999. All rights reserved. Printed in USA 3/99. VXA, Discrete Packet Format, Variable Speed Operation, OverScan Operation, and "It's all about restoring your data" are trademarks of Ecrux Corporation.



Avax International

8 Thompson Crescent

Erin, Ontario N0B 1T0

519-833-2900 or 800-443-4542

Fax - 519-833-7469

Web - www.avax.com

email - sales@avax.com